

1 (April 5, 2004)

2 **Light Standards with Type 2 Luminaire Arms**

3 Lighting standards shall be fabricated in conformance with the methods and
4 materials specified on the pre-approved plans listed below provided the following
5 requirements have been satisfied:
6

7 (a) Light source to pole base distance (H1) shall be as noted in the Plans.
8 Verification of H1 distances by the Engineer, prior to fabrication, is not
9 required. Fabrication tolerance shall be ± 150 millimeters for H1 distance
10 and ± 50 millimeters for mast arm length.
11

12 (b) All other requirements of the Special Provisions have been satisfied.
13

14 <u>Pre-Approved Plan</u>	15 <u>Fabricator</u>	16 <u>Mounting Hgt.</u>
17 Drawing No. W3720-1 18 & W3720-2	Ameron Pole Prod. Div.	12.2 m & 15.2 m
19 Drawing No. DB00653 20 Rev. A Sheets 1, 2 & 3	Valmont Ind. Inc.	9.2 m, 12.2 m, & 15.2 m
21 Drawing No. NWS 3515 22 or NWS 3515B	Northwest Signal Supply Inc.	7.5 m, 9.2 m, 10.7 m, 12.2 m, 13.7 m, & 15.2 m
23 Drawing No. LD-10095 24 Rev. 20 Sheets 1 & 2	Union Metal Corp.	12.2 m
25 Drawing No. LD-10100 26 Rev. 15 Sheets 1 & 2	Union Metal Corp.	15.2 m
27 Drawing No. WS-SL-02	American Pole Structures, Inc.	7.5m, 9.2m, 10.7m, 12.2m, 13.7m & 15.2m